

## DL3L Series



### Ordering Informations

Model No.	Color	Size	Light Source	Luminous Intensity
DL3LWW3W	Warm White (3,000-3,500K)	Ø80x27.5mm	3x1W	230-270lm
DL3LWE3W	Cool White (6,000-6,500K)	Ø80x27.5mm	3x1W	280-310lm

### Outline Drawing




DL3L Series



### Features

- Aluminum casing with special extrusions design
- Energy saving
- Eco-friendly product
- Long life time
- High luminance
- Low power consumption
- RoHS compliant
- Low surface heat against hand touch
- No UV or IR damage light sensitive items
- Highly efficient heat release mechanism



AC 85-220V, 50/60Hz  
Supply unit

\* The dimensional outline drawings are common in (DL3LWW3W and DL3LWE3W)

Unit: mm

### Specifications

Parameter	Rating value
Power Consumption	3W
Input Voltage	AC 85-220V, 50/60Hz
Installation Diameter	66.0mm
Light Source	3x1W power LED
Operating Temperature	- 40 to +70°C
Beam Angle (Adjustable tilt)	30°(15°)
Weight	258g
CRI	85
Body / Finish Color	Die-cast Aluminium casing

#### Warning:

- \* Do not look permanently to the light sources.
- \* Specified performance measured in 85-220Vac.

